



# ROLLER STRIKER

## HYDRAULIC POWERED

QUALITY ENGINEERED. QUALITY BUILT. QUALITY SURVIVES.

### TECHNICAL DATA

Weight (Drive & Opp. Handles) 22kg  
 Motor Power (hp) 3 Hp  
 Max. Drive Speed 500 Rpm  
 Pressure Required (Bar) 140 Bar  
 Flow Rate (l/min) 30l/min  
 Vibration (m/s<sup>2</sup>) 4.00 m/s<sup>2</sup>  
 Danfoss Hydraulic Components  
 ISO/IEC 17050-1 Declaration of Conformity  
 Hydraulic Hose & Assembles  
 SAE J1273/SAE J517  
 Hydraulic Adaptors,  
 ISO 8434-6/BS 5200  
 Quick Release Couplings,  
 ISO 1628 / Amd 1;206E



The MBW Roller Striker is a fast, efficient, highly versatile and modern alternative way to strike off and finish large floor areas of newly laid concrete. Tubes of varying sizes are fitted to a hydraulically powered drive handle, which in turn, spins the tube over the top of the newly laid surface. The tube rotates in the opposite direction of travel, creating a positive grasp of friction, gathering a build up of up to 150mm of concrete, which tumbles ahead of the spinning tube. The net effect of this method of operation is that the major aggregates remain near the surface, unlike alternative screeding techniques, which in turn results in a more dense and durable slab. The Roller Striker is quick and easy to set up, use and clean.



# ROLLER STRIKER

## HYDRAULIC POWERED

QUALITY ENGINEERED. QUALITY BUILT. QUALITY SURVIVES.

### ACCESSORIES - TUBES AVAILABLE IN THE FOLLOWING SIZES:

- 3.66M (12") ROLLER STRIKER TUBE (ONLY) 41KG
- 4.26M (14") ROLLER STRIKER TUBE (ONLY) 48KG
- 4.88M (16") ROLLER STRIKER TUBE (ONLY) 54KG
- 5.49M (18") ROLLER STRIKER TUBE (ONLY) 60KG
- 6.10M (20") ROLLER STRIKER TUBE (ONLY) 66KG
- 6.71M (22") ROLLER STRIKER TUBE (ONLY) 73KG
- 7.32M (24") ROLLER STRIKER TUBE (ONLY) 79KG

