

# REVERSIBLES

## GPR65/68

The GPR65 and GPR68 are compact reversible plates ideal for narrow trenches and confined areas and are high production plates. Travel speeds up to 92 ft/min are achieved with good compaction conditions and the plates move with ease over irregular lift surfaces. Head-to-head competitive demonstration quickly establishes the comparative benefits of the GPR65 and GPR68.

Model	GPR65	GPR68
Plate Size WxL	53 x 56 cm (21 x 22 in)	53 x 56 cm (21 x 22 in)
Operating Weight	Petrol: 148 kg (325 lbs) Diesel: 165 kg (365 lbs)	Petrol: 150 kg (330 lbs) Diesel: 168 kg (370 lbs)
Engine	Petrol Honda GX160 or Diesel Hatz 1b20	Petrol Honda GX160 or Diesel Hatz 1b20
Amplitude	1.83 mm (.072 in)	1.80 mm (.071 in)
Centrifugal Force**	27 kN (6000 lbs)	27 kN (6000 lbs)
Exciter Speed	4400 vpm	4400 vpm
Compaction Depth*	Up to 56 cm (22 in)	Up to 56 cm (22 in)
Travel Speed	Up to 28 m/min (92 ft/min)	Up to 27 m/min (88 ft/min)
Compaction Area	641 m <sup>2</sup> /hr (6900 ft <sup>2</sup> /hr)	736 m <sup>2</sup> /hr (7920 ft <sup>2</sup> /hr)

\* Clean sand, optimum moisture. MBW recommends that lifts not exceed 12".

\*\* Centrifugal force is not a measure of compaction performance.

() Imperial measurements. Specifications subject to change without notice.



**GPR65**



**GPR68**



## GPR44/57

The GPR44 and GPR57 are high quality, price-competitive reversibles. These plate compactors offer outstanding compaction performance and can be easily transported and stored when not in use.

Model	GPR44	GPR57
Plate Size WxL	48 x 35cm (19 x 14 in)	70 x 43cm (28 x 17 in)
Operating Weight	80 kg (176 lbs)	180 kg (397 lbs)
Engine	Petrol Honda GX160	Diesel Yanmar L70 - Electric start
Centrifugal Force**	15 kN (1530 kgf)	27 kN (2750 kgf)
Vibration Frequency	100 Hz (6000 vpm)	90 Hz (5400 vpm)
Compaction Depth*	Up to 56 cm (22 in)	Up to 56 cm (22 in)
Travel Speed	Up to 25 m/min (82 ft/min)	Up to 25 m/min (82 ft/min)

\* Clean sand, optimum moisture. MBW recommends that lifts not exceed 12".

\*\* Centrifugal force is not a measure of compaction performance.

() Imperial measurements. Specifications subject to change without notice.

**GPR44**



**GPR57**





## GET IN TOUCH.



### EMAIL

All Enquiries - [ukoffice@mbw.com](mailto:ukoffice@mbw.com)  
Sales - [saleseurope@mbw.com](mailto:saleseurope@mbw.com)



### LOCATION

MBW Europe Ltd  
Units 2 & 3 Cochrane Street,  
Bolton, UK - BL3 6BN



### PHONE

+44 (0)1204 387784

[WWW.MBWEUROPE.COM](http://WWW.MBWEUROPE.COM)

